## **Norco Hydraulic Bottle Jacks**

Fifty-percent safety overload factor. Easier to repair than threaded jack designs. Fewer working parts, internally machined oil passages, extremely smooth bearing surfaces and close tolerances ensure longer life, fewer breakdowns. No-leak "Uniweld" construction. Carrying handle included.

**0410191** 12 Ton Standard; 4/Ctn. **0410190** 12 Ton Shorty; 4/Ctn.

**0410192** 20 Ton: 4/Ctn.

**0410196** Repair Kit f/20 Ton: 76520,

76820 (2-9/16" plunger)

**0410189** Repair Kit f/12 Ton (2-9/16" plunger)

0410193 Oil Filler Plug; 25/Ctn.

**Air Hydraulic Jacks** 

Equipped with U.S. Patented air motor kit for quick and easy lifting. Quick connector hose provides easy removal of air hose. Uses standard shop air. Minimum height: 9.5" H; maximum: 18-5/8" H.

**0410050** 12 Ton; 26 lbs. **0410051** 20 Ton; 35.2 lbs.





Hook it up, pull it tight, and zip! It's done! The quickest, toughest, safest tie-down on the market.

- Lightweight yet strong, heavy duty 3/8"
- · Self-locking, quick release
- Cinches tightly in place without knots or buckles
- · All parts are corrosive-resistant
- Easy-release trigger is recessed to prevent accidental triggering
- Rubber-coated hooks protect vehicles and prevent slipping
- Safer than bungees with no slap-back or snapping
- 8' length of rope

0342107



Displays available





- ◆ 1/2" 100% recycled polyethylene plastic
- Virtually indestructible, even in harsh conditions
- Double-sided, skid and slip resistant
- Low cost alternative to fiberglass mats
- Easily portable
- Maintenance free
- 6 Year Warranty from date of purchase

Get vehicles and equipment over lawns, through mud and across soft terrain while saving labor, bog-down time, towing charges and ground restoration fees—perfect for set-ups.

0265301 2' x 4' 0265303 2' x 8' 0265302 2' x 6' 0265304 4' x 8'

J-1

## **Transport Lights**

## Low profile light bars:



Four Halogen rotator model with two diamond mirrors. Redesigned reflector with pre-focused halogen bulb for more light intensity. 110 RPM per rotating module. Relampable 50 watt equivalent intensity (35 watt halogen) bi-pin bulb. Shatter-resistant polycarbonate outer lens, amber warning color.

0340855 48" Wide (9404h)

## **Amber Minibar**



Shatter-resistant polycarbonate outer dome,

non-corroding molded nylon base, low current consumption, easy to service with modular parts. 55 watt Halogen light, 8 amp draw. 17" x 4.75".



**0340856** Permanent Mount (9200ha)

0340857 Magnetic Mount, Adapter & Cord (9200hma)

**0340859** Replacement Bulb (2073-795)

## 360° 2-Color Minibar



Rugged aluminum 16" minibar with two 360° quad flash strobes, one wall mirror. 11.25 joules. Flash rate of 75 quad flash sequences per minute, per self-contained strobe @22 watts. 5.5" H x 16" L x 8.5" D.

**0340862** (9216s-boy)

## **360° Strobe LED Beacon** with Flange Mound



Standard 360° LED beacon (nine 1 watt LEDs), flange mount, short lens.

- 10 Customer selectable flash patterns
- Synchronizing capabilities between 0340840 and 41
- Extremely low current draw
- Durable polycarbonate, Twist-Off Lens
- Features a durable and lightweight polycarbonate, universal flange base
- Completely encapsulated circuit for increased weather and shock resistance

**0340840** Permanent Mount (255tsl)

0340841 Vacuum Magnetic Mount, Adapter & Cord (255tsvI)

## **360° Strobe Beacons**





Versatile & powerful with 5.5" amber lens and computer designed optics. Universal anodized aluminum mounting base. Accommodates surface, pipe or magnetic mount options. Magnetic mount version includes metal disk with Velcro and cigarette-plug adapter with cord. Double flash.

**0340850** 5.5" High (240cfda-u)

**0340851** 4 1/2" H, Magnetic Mount (240smd-u)

0340852 Replacement Flash Tube (129)



## **Selectable Double or Quad Flash**

Field selectable flash pattern via internal jumper: standard quad flash or selectable double flash. Virgin Lexan, twist-off lens. Durable and lightweight polycarbonate plastic universal flange base. Completely encapsulated circuit for increased weather and shock resistance. Automatic low voltage shutdown below 9.5V DC. Operates automatically 12V DC - 48V DC. Amp draw: 2.0 Amps at 12V DC. Joule rating: 7 joule double flash; 10 joule quad flash. Flash rate: 80 DFPM/65 QFPM. 4-3/4" tall x 6-13/32" dia.

0340860 (255ts)



## **Safety Signs**

## **Vinyl Double-Sided Sign**



Features a strong 1/4" poly rope sewn the entire length; all the stress goes to the rope, not on the sign, so there are no grommets to tear out. 12" high letters are screen printed black on interstate yellow. "Oversize Load" on one side & "Wide Load" on the other.

**0342016** 20" x 84"; 25/Ctn.

## **Metal Double-Sided Sign**



Light-weight metal alloy sign. Baked-on enamel finish, scratch resistant. Will not fade, crack, peel or rust. Custom-designed fold for easy storage. Black on interstate yellow. 12" letter height and 2" letter stroke.

0342009 15" x 6' **0342010** 18" x 7' (PA Approved)

## **Oversize Load (Ohio DOT)**

# **OVER SIZE LOAD**

Vinyl mesh open weave meets Ohio DOT regulations. 12" x 60" with 8" letters.

0342003

## **Poly-Coated Fabric Highway Signs**

Long lasting, durable and weatherproof, reinforced metal grommets, double stitched seams and Tyvek corners for extra strength. Attaches easily with shock cords. Black letters on interstate yellow background.



Cloth sleeve numbered 10, 12, 14 and 16 enables sign to address every Arkansas sign requirement. Letter height 12", stroke 2".

**0342001** Over Size XX Load, 18" x 7'; 25/Ctn.

## **OVER SIZE LOAD**

0342002 Over Size Load; 18" x 8', Michigan Approved; 25/Ctn.



**0342005** Danger - Wide Load Ahead, 18" x 4': 25/Ctn.



0342007 Danger - Wide Load Follows, 18" x 4'; 25/Ctn.

Coatings & Cleaners

## **Towing Safety Flags**

## **Red Flag & Clip Kit**

Meets regulations. Two bright red ravel-proof nylon tricot flags and two plastic flag clips. Clear-bagged.

0341907 18" x 18" 0341908 24" x 24"



**Plastic Clips** 

0341909 Each 0341904 Bag of 25; 40/Ctn.

## **Red Flag**

Red tricot nylon, plain edges. High level of reflectancy. In packs of 6, 240/Ctn.



**0341911** 18" x 18" **0341912** 24" x 24"

## Flag & Staff

Nylon tricot flag mounted on heavy-duty 36" staff. Ideal for front of tow trucks where required. 24" x 24".

0341905

## **Flag Holder**

Galvanized steel, bolt-on mount. Thumb screw holds secure. All hardware included. 24/Ctn.

0341906



Breathable, microporous film laminate. Passes NFPA 99 criteria for antistatic materials

0345038 white, one-size, 200/case



Dust Mask

metal nose band to ensure a

**0345055** white, one-size

secure seal and comfortable fit.

types of dust. Lightweight, easy to

use. Single fixed strap. Adjustable

**Tarp Straps** 

Trucker's hard rubber snubbers with iodized S-hooks for superior resiliency and long life.


0342102 15": 50/Ctn. 0342103 22"; 50/Ctn. 0342104 31"; 50/Ctn.

## **KleenGuard A20 Coveralls**

**Breathable Particle Protection Apparel** 

KleenGuard A20 Coveralls are made from Microforce Barrier SMS, a breathable fabric that provides improved barrier protection on submircronsized particles for a perfect combination of protection and comfort.

The tough, durable cloth-like outer layer is an abrasion-resistant, spunbond polypropylene and the middle layer is an intricate web of microfibers that filter out light, water-based liquids and dry particulates. These white coveralls are ideal for maintenance and general clean-up work, including asbestos handling, lead abatement and fiberglass/cellulose insulation operations.



Zipper Front Elastic: Back. Wrists & Ankles



KleenGuard Hooded A20 Coveralls					
Stock #	Color	Size	Case Qty		
0345041	White	Large	24		
0345042	White	X Large	24		
0345043	White	2X Large	24		
0345044	White	3X Large	20		
0345045	White	4X Large	20		

# Heating & Cooling

## **All Leather Work Gloves**

All Leather Work Gloves

- Front, back & leather cuff
- Double leather palm
- Double Stitched
- · Sold as pairs with hang-up display cards



0345016

0340509\*

## **Leather Palm Work Gloves**

Full leather palm with leather knuckle band & fingers. Split leather cowhide. Double stitched. Heavy canvas gauntlet cuff for added protection. Sold as pairs with hang-up display cards.

0345015



Rubber **Knee Pads** 

Rubber Knee Pads with Elastic Velcro® Straps. Quick and easy on/off with 2" wide single elastic Velcro straps.

0345010



## **ABC Extinguishers**

4 lbs 12oz.: 6/Ctn

Multi-purpose. Non-toxic tri-class dry chemical agent (monoammonium phosphate) fights flammable liquids & electrical fires as well as wood, paper and cloth fires. Recommended for commercial use.

Multi Purpose Home UL rated:1-A:10-BC: Effective on wood, paper, plastic, flammable liquid and electrical fires. Mounting bracket with strap included. 0340508\* 2 lbs 9.3 oz.; 6/Ctn.

**Heavy Duty. Multi Purpose, for Home, Office or Business** Rechargeable (fits easily inside standard fire box-fire box not included). Exceeds NFPA 10 Minimum Code Requirements. UL rated 3-A:10-B:C for trash, wood, paper, liquids, electrical fires.



**Smoke Alarm AC Powered** 

120VAC. ionization sensor. meets U.L. Standard 217. Interconnectable. Quick connect wiring harness and Fast Install mounting bracket. Outside diameter is 5-3/8" for better coverage of cutouts.

0141302 Electric (mfg# 9120) 0141305 Electric with 9V Battery

Back-up in side drawer. (mfg# 9120B)



## **BC Extinguisher**

Recreational. Fights flammable liquids and electrical fires. UL rated 5-B:C. Large, easy to read gauge. Sodium bicarbonate. Rechargeable. Mounting bracket with strap included.

0340501\* 2 lbs.; 6/Ctn.

Garage and Home. UL rated 10-B:C. Fights grease, oil and electrical fires. Large, easy to read gauge. Includes Ergonomic handle and trigger. Sodium bicarbonate. Mounting bracket with strap included.

**0340507\*** 2 lbs, 7 oz.; 6/Ctn.



0340507

### Smoke Alarm **Battery Powered**

Hinged cover for easy battery replacement. Lighted Power & Alarm indicator. Silence feature.

Tamper resistant locking pin. 10 year limited warranty



0141303 Carbon Zinc Battery FG250B 0141301 Lithium Battery - FG250LB

## **Kitchen Fire Extinguishers**



UL rated 5-BC made especially for the kitchen. White with white mounting cap and pop-up pressure indicator. Effective on oil, flammable liquids and electrical fires. Specialty quick release mounting cap. Non-corrosive. Easy to clean up.

0340510\* 1 lb 5.3 oz; 6/Ctn.

## **Carbon Monoxide Detector**

#### w/Lithium Battery Tamper Resistant

- · Lithium Battery Powered
- Electrochemical Sensor
- · Sensor Life Monitor
- Tamper-Resistant
- ANSI/UL 2034-09 Listed
- · CSA and IAS Certified
- NFPA 720 Compliant
- Five Year Warranty

0250120 Battery Powered 0250121 Plus Digital Display



## **Carbon Monoxide Detector**

#### Plug-In with 9v Battery Back-Up. Digital Display

Plug-in carbon monoxide alarm with digital display and 9V battery backup meets most state and local codes for carbon monoxide alarms.

Electrochemical Carbon Monoxide Sensor - the most accurate sensor available as compared to other sensing technologies.

- Single Button Test/Silence
- Battery Backup
- Two silence features can silence the low-battery chirp for up to eight hours or temporarily silence an unwanted nuisance alarm
- Digital Display shows visual confirmation of CO levels in PPM
- Peak Level Recall Button recalls the highest level of Carbon Monoxide detected
- 5-Years Limited Warrant

0250108 Plug-In, 9v Back-Up





#### Combo Alarm Smoke Detector & Carbon Monoxide **Detector**

0250106 Battery Powered

First Alori

0250104 Plug-In w/Battery Back-Up

(2 - AA batteries)

(2 - AA batteries)

**Carbon Monoxide** 

**Detector** 

0250104

0250105

Samples air once every second

Calibrated at four levels for accuracy

Silencer button, re-alarms if levels persist

Unique self testing system alerts if malfunctions.

Battery Powered. The BRK First Alert **Combination Carbon** Monoxide and Smoke Alarm protects you from the very real dangers of both fire and smoke as well as

0250105 Plug-In




0250106

carbon monoxide. 0250103 Battery Powered Use 2-AA Batteries

## **Triangle Cast Equalizer**


Rugged cast. Use 1/2" or 9/16" dia. shackle bolts.

Stock #	Α	В	С	D
0157170	6"	4"	9/16"	1-3/4"





OSCS 1/2 OF S/ TO CIA: SHACKIC BOILS.						
Stock #	Α	В	С	D		
0157164	5-5/8"	2-13/16"	9/16"	9/16"		



## **U-Bolt w/Nut**

1/2" dia. for mounting to 3" dia. axle tube. Selflocking nuts included.

0156915 mono-leaf spring 0156925 four-leaf spring

## **Bearing Cup**



## **Bearing Cone**

L 68149, high grade alloy steel. Shaft dia. 1-3/8" 0157184

LM 67048, high grade alloy steel. Shaft dia. 1-1/4'

0157188



0157182 L 68111

## **Shur-Set III**™ **Breakaway Kit**

Mounts on jackpost or A-frame. Quick, easy, one-bolt installation—no cutting or drilling needed. Rust-proof polyethylene plastic case protects battery and charger from elements and corrosion. Meets or exceeds DOT specifications regarding breakaway/ holding requirements.

Complete kit includes: battery case with mounting bracket; 12V sealed, rechargeable battery; and nylon breakaway switch. Battery charger sold separately.



**0340105** Breakaway Kit; 10/Ctn. 0340103 Switch Only; 20/Ctn.

## **Lug Bolt**

1/2" dia. For use with cast hubs that are



drilled and tapped. 0154109 1/2 - 13 threads.

2-1/4" long. 0153108 1/2 - 20 threads. 1-7/8" long.

## **Lug Stud**

Plated 1/2" dia., 2" long, 1/2-20 threads. Fits only Continental axles with formed steel hubs.

0157124

## **Spring Hanger** 1/4" thick heavy steel, for use w/1-3/4" wide spring.

0340106 Battery Charger

**0157161** 3" long, drop 2-1/4". For use with 9/16"

or 1/2" dia. shackle bolt.

**Breakaway Switch** 

corrosion free to assure long life. Silver contact points remain

corrosion free for positive contact. Nylon pull-pin can't freeze up,

Sets trailer brakes in case of accidental trailer breakaway. Trailer brakes are applied automatically.

assuring positive activation.

0340103

Reinforced nylon case. Rust and

**Battery Charger** 

12 volt. Fits securely in battery case with battery. Compatible with all automotive

overcharging. Designed to provide exact

electrical systems. Automatic shutoff prevents

amperage needed to sealed, wet cell battery.

**0157168** 1-3/4" long, drop 1-1/8". Use only at

shackle end of single axle suspensions.

0157160 13" long, drop 3-1/4". Use with 9/16" or

1/2" dia. x 3" shackle bolt.

1/4" thick steel, 1-1/4" wide. Use with 1/2" or

9/16" dia. shackle bolt to connect to equalizer

## Shackle **Bolt & Nut**

Steel, 9/16" dia, and 3" long. Hex lock nut included.

0157166

## **Lug Nut**

Plated steel, 1/2" with 20 threads per inch. Heavy

0157130



## **Universal Rim Clamp**

Heavy-cast. Universal, will fit most mobile home axles, fits axles using either lug bolts or lug studs. Sometimes referred to as wedges.



0157125

## **Dust Can**

Universal plated, will fit most axles, keeps grease in and dirt out to protect bearings.



0156900

## **Spindle Nut**

**Shackle Link** 

0157162 2-9/16" Hole Center 0157163 2-1/4" Hole Center

or to spring hanger.


Universal assembly comes with 1" dia. washer, 1/8" x 1-1/2" long cotter pin, and 1" dia. slotted hex nut.



0157172

## **Grease Seal**

ABS plastic, long-wearing. (Refer to old seal dimension before ordering).



**0157174** 2-9/16" OD. 1.840" ID lip seal.

**0157176** 3-3/8" OD, 2.245"

ID lip seal



Anchors & Outdoor Set-Up Material Improvements

Doors & Windows

Coatings & Cleaners

Appliances Tools & Hardware

Carpet & Flooring

Electrical

Plumbing

Heating & Cooling